



**LEDBURN CABLES IS  
AN INDEPENDENTLY  
OWNED CABLE  
DISTRIBUTOR.**

## **TRUSOUND DMX CABLE**

*Developed to ensure accurate transmission of digital AES/EBU audio signals and digital DMX control signals, these cables are used extensively in the entertainment industry.*



Developed to ensure accurate transmission of digital AES/EBU audio signals and digital DMX control signals, these cables are used extensively in the entertainment industry. DMX is designed to work between 90Ohm and 120Ohm impedance. The level of shielding enables interference-free transmission even over long distances.

# Technical Information

<b>Conductor Resistance:</b>	<87.2 Ohm/km
<b>Capacitance:</b>	Core to core: 47 pF/m
<b>Impedance:</b>	110 Ohm
<b>Test Voltage:</b>	
<b>Core to core:</b>	1200V
<b>Core to screen:</b>	500V
<b>Working Temperature:</b>	-20°C to +70°C
<b>Attenuation/100m:</b>	Frequency: 1MHz: 2.3dB, 3MHz: 3.9dB, 10MHz: 6.9dB

# Specification

Part No.	Pairs x mm <sup>2</sup>	No. of Power Cores x mm <sup>2</sup>	Weight kg/km	O/D mm	Colour
<b>TSD02010</b>	1 x 2 x 0.22		50.00	6.0	BLACK
<b>TSD02011</b>	1 x 2 x 0.22		50.00	6.0	BLUE
<b>TSD02020</b>	2 x 2 x 0.22		75.00	8.0	BLACK
<b>TSD021110</b>	4 x 2 x 0.22	3 x 1.5	375.00	17.4	BLACK
<b>TSD02150</b>	1 x 2 x 0.22	3 x 1.5	175.00	11.6	BLACK
<b>TSD022110</b>	4 x 2 x 0.22	3 x 2.5	460.00	19.3	BLACK
<b>TSD02250</b>	1 x 2 x 0.22	3 x 2.5	220.00	13.3	BLACK
<b>TSD02270</b>	2 x 2 x 0.22	3 x 2.5	380.00	18.3	BLACK